

c12) **United States Patent**
Magana

(IO) **Patent No.:** **US 10,723,521 B2**
(45) **Date of Patent:** **Jul. 28, 2020**

(54) **CONTAINER ASSEMBLY**

(71) Applicant: **Direct Pack, Inc.**, Sun Valley, CA (US)

(72) Inventor: **Leonardo Magana**, San Bernardino, CA (US)

(73) Assignee: **Direct Pack, Inc.**, Sun Valley, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 462 days.

(21) Appl. No.: **15/184,226**

(22) Filed: **Jun. 16, 2016**

(65) **Prior Publication Data**

US 2016/0368669 A1 Dec. 22, 2016

Related U.S. Application Data

(60) Provisional application No. 62/180,298, filed on Jun. 16, 2015.

(51) **Int. Cl.**

B65D 8/00 (2006.01)
B65D 43/102 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC.....**B65D 43/10204** (2013.01); **B65D 11/120** (2013.01); **B65D 21/0233** (2013.01);
(Continued)

(58) **Field of Classification Search**

CPC..... B65D 43/0206; B65D 21/0234; B65D 21/00212; B65D 43/204; B65D 11/20;
(Continued)

(56)

References Cited

U.S. PATENT DOCUMENTS

2,986,300 A 5/1961 Parrish
2,999,611 A 9/1961 Paulson
(Continued)

FOREIGN PATENT DOCUMENTS

CA 1072464 A 2/1980
CA 2127311 C 3/1995
(Continued)

OTHER PUBLICATIONS

International Search Report and Written Opinion dated Sep. 6, 2016 for Application No. PCT/US2016/037838, 10 pgs.

(Continued)

Primary Examiner - Elizabeth J Volz

(74) *Attorney, Agent, or Firm* - Frost Brown Todd LLC

(57)

ABSTRACT

The present disclosure relates to a container assembly formed from a first shell component and a second shell component releasably locked together. The first shell component includes a first side wall, a first outer wall, a first male locking portion, and a first female locking portion. Similarly, the second shell component includes a second side wall, a second outer wall, a second male locking portion, and a second female locking portion. To form the container assembly, a user rotates the two shell components to be oriented 180-degrees with respect to one another and presses the two shell components together. Upon pressing, the first male locking portion is configured to releasably lock with the second female locking portion while the first female locking portion is configured to releasably lock with the second male locking portion to releasably hold the two shell components together.

20 Claims, 13 Drawing Sheets

